

Design & Manufacture
of Protection Systems for power lines used on:

Straps and Buckles



Stavol™

LUHFSER™

Stavol™

Stavol™



STRAPS

WIDTH	THICKNESS	LENGTH	WEIGHT
9.53 mm (3/8")	0.64 mm	30.48 mts (100 feet)	1600 grs
12.70 mm (1/2")	0.76 mm	30.48 mts (100 feet)	2300 grs
15.88 mm (5/8")	0.76 mm	30.48 mts (100 feet)	3000 grs
19.05 mm (3/4")	0.76 mm	30.48 mts (100 feet)	3500 grs



BUCKLES

WIDTH	THICKNESS	TOLERANCE	WEIGHT	TENSION
9.53 mm (3/8")	1.27 mm	+/- 0.13 mm	3.5 grs	180 Kgf
12.70 mm (1/2")	1.27 mm	+/- 0.13 mm	8.2 grs	350 Kgf
15.88 mm (5/8")	1.59 mm	+/- 0.15 mm	11.7 grs	450 Kgf
19.05 mm (3/4")	1.98 mm	+/- 0.18 mm	16.3 grs	500 Kgf



Test Certificate



Our **Stavol™** line of products are the result of extensive research and development. We have selected the best stainless steels which are subjected to stringent laboratory tests and static load tests up to a ton of load.

Dimensions

CLAMPS



DESCRIPTION	LENGTH
Ready-to-use Clamps 3/8" (9.50 mm) Thickness 0.68 mm	1.30 mts 1.10 mts 0.80 mts 0.70 mts
Ready-to-use Clamps 1/2" (12.70 mm) Thickness 0.76 mm	1.30 mts 1.10 mts 0.80 mts 0.70 mts
Ready-to-use Clamps 5/8" (15.80 mm) Thickness 0.76 mm	1.30 mts 1.10 mts 0.80 mts 0.70 mts
Ready-to-use Clamps 3/4" (19.00 mm) Thickness 0.76 mm	1.30 mts 1.10 mts 0.80 mts 0.70 mts

CONTACT

Phone: (01157)(1) 337 8736 - 337 7939 - Fax: 337 7945
Mobile: (01157) 311 591 4043 - 311 591 3600
gerencia@electricosinter.com - combeau@attglobal.net
Headquarters: Calle 17 No. 42A - 69
Bogotá D.C. - Colombia



www.electricosinter.com